

EACH European Association of Geosynthetic product Manufacturers

COMPARATIVE LCA OF GEOSYNTHETICS versus CONVENTIONAL CONSTRUCTION MATERIALS CASE 4: SOIL RETAINING WALL

Andreas Elsing - Huesker Synthetic (on behalf of EAGM) Ian Fraser – Tensar International (on behalf of EAGM)

The E.A.G.M. commissioned ETH Zürich and ESU-services Ltd. to quantify the environmental performance of commonly applied construction materials. A comparison was undertaken between:

- conventional materials like concrete, cement, lime or gravel
- geosynthetic materials

A set of Comparative Life Cycle Assessment studies are carried out concentrating on various civil application cases, namely:

- filtration (case 1)
- foundation stabilised road (case 2)
- landfill construction (case 3)
- slope retention retaining structures (case 4)



CHARACTERISATION OF ALTERNATIVES



4A Retaining concrete wall reinforced with steel (strength class B300)

4B Soil wall reinforced with geosynthetics (LTDS 14 kN/m)



CHARACTERISATION OF ALTERNATIVES

Soil retaining wall

The 'average' of 3 types of different geosynthetics is modelled:

- extruded stretched grids
- laid (welded) grids
- woven / knitted grids

(Data collected from EAGM members 2010)





Bridge abutment reinforced concrete



EXAMPLES/PICTURES OF THE ALTERNATIVES



Retaining wall reinforced with concrete



Soil wall reinforced with geosynthetics



EXAMPLES/PICTURES OF THE ALTERNATIVES



Green facing



Life cycle impact Infrastructure element

Selected key figures referring to the construction of reinforced concrete wall (4A) and geosynthetic reinforced soil structure (4B)

		4A	4B
	Unit	Concrete	Geosynthetics
Concrete, sole plate and foundation	m³/m	1.60	-
Lean mix concrete	m³/m	0.24	-
Structural concrete	m³/m	2.10	0.31
Reinforcing Steel	kg/m	153	-
Geosynthetic	m²/m		39.2
Diesel in building machine	MJ/m	11.6	53.9
Transport, lorry	tkm/m	701	265
Transport, freight, rail	tkm/m	33.2	6.9
NMVOC emissions (bitumen)	g/m	20	

Indicators investigated: Acidification, Eutrophication, Global Warming, Photochemical oxidation, CED non-renewable, CED renewable, Particulate matter, Land competition & Water use



European Association of Geosynthetic product Manufacturers

Environmental impact graph





THIS STUDY SHOWS

The use of geosynthetics leads to:

- lower impact in all categories
- ~ 75% reduction of Non renewable cumulative energy demand (CED)
- ~ 85% reduction of cumulative greenhouse gas emissions
- Every 3 linear meters soil retaining wall (3 meter high) saves 30,000 MJ eq, which is equivalent to the energy consumption of one household per year!

The whole study including the results of the critical reviews is available on: <u>http://www.eagm.eu/</u>